





PinPoint™ systems offer the most advanced technology available in tool control. The AeroRACK™ cabinet is ideal for use in manufacturing, MRO and line maintenance operations. Designed to support multiple users and available in a variety of widths and storage compartment configurations.

Features and Benefits	
Simple operation	Automated technology ensures individual accountability and compliance without interfering with technicians' workflow
Flexible design	Available in a variety of common standard cabinet widths and storage compartment configurations. Each can be configured with custom tool layout to meet your unique requirements.
Complete compatibility	PinPoint is adaptable to existing tools so there's no need to purchase new ones to gain electronic monitoring capability.

Users gain access to the AeroRACK™'s contents by swiping their personal ID card at the AeroRACK™ access console. The system will recognize the technician's assigned authorization level and unlock only the permitted compartments. After removing the required items, the technician simply closes the door and pushes a button to end the session. With no additional manual data entry necessary, the AeroRACK™ maintains constant real-time inventory of the items checked out. The tool return process is just as simple and just as fast. Cabinet contents can be managed remotely, monitoring calibration status, and tool condition.

Aero**RACK**™





Contact information

Birger Olsen Director of Sales Aircontact Services AS +47 95802550 birger.olsen@acs.no



RFID

- ISO 18000-6C EPC Gen 2 900 MHz
- ISO 18000-3 13.56 MHz

Power Requirements

Voltage: 100-250 V Frequency: 50/60 Hz Current: <5 amps

User Authentication:

RFID Proximity card 125 kHz or 13.56 MHz - Numerous formats supported.

Environmental:

Ingress Rating: IP-41

Operating Temperature: 0°C -> 50°C (Optional extended tem-

perature range)

Storage Temperature: -20°C -> 70°C Humidity: 90% Maximum (Non-condensing)

Computer:

Processor: IntelTM 15

OS: Windows™ 7 Professional

Display: 10.1" 1024 x 768 - Resistive Touch Screen

Storage: mSATA Solid State 64 GB **Network:** Ethernet 10/1000 Base-T

Approvals:

FCC Class A: CFR47 Part 15 CE: EC 6100-6-2 / 6100-6-4 C-Tick: AS/NZS CISPR 22-2009

Software:

- Available full-featured PINPOINT™ tool control software
- Full administration and configuration
- Comprehensive reporting
- Remote unit inventory status